

GENERAL ENGINE DATA

Type	4-Cycle, Water Cooled	
Aspiration	Turbo-Charged, Inter Cooler (Fresh water to Cooler)	
Cylinder Arrangement	60°V	
No. of Cylinders	12	
Bore mm(in.)	150	(5.91)
Stroke mm(in.)	175	(6.89)
Displacement liter(in ³)	37.11	(2265)
Compression Ratio	14.5:1	
Dry Weight - Engine only - kg(lb)	4300	(9482)
Wet Weight - Engine only - kg(lb)	4560	(10055)

PERFORMANCE DATA

Steady State Speed Stability Band at any Constant Load		
Electric Governor - %	±0.25 or better	
Maximum Overspeed Capacity - rpm	2000	
Moment of inertia of Rotating Components - kgf·m ² (lbf·ft ²)	55.6	(1319.6)
(Includes Std. Flywheel)		
Cyclic Speed Variation with Flywheel at 1800rpm	1/523	

ENGINE MOUNTING

Maximum Bending Moment at Rear Face of Flywheel Housing - kgf·m(lbf·ft)	200	(1446.9)
---	-----	----------

AIR INLET SYSTEM

Maximum Intake Air Restriction (Includes piping)		
With Clean Filter Element - mm H ₂ O (in.H ₂ O)	400	(15.7)
With Dirty Filter Element - mm H ₂ O (in.H ₂ O)	635	(25.0)

EXHAUST SYSTEM

Maximum Allowable Back Pressure - mm H ₂ O (in.H ₂ O)	600	(23.6)
---	-----	--------

LUBRICATION SYSTEM

Oil Pressure at Idle - kgf/cm ² (psi)	2 ~ 3	(29 ~ 43)
at Rate Speed - kgf/cm ² (psi)	5 ~ 6	(71 ~ 86)
Maximum Oil Temperature - °C(°F)	110	230
Oil Capacity of Standard Pan	High - liter (U.S.gal)	180 (48)
	Low - liter (U.S.gal)	150 (39.6)
Total System Capacity (Includes Oil Filter) - liter (U.S.gal)	200	(52.8)
Maximum Angle of Installation (Std. Pan)	Front Down	9.5°
(Engine Only)	Front Up	11°
	Side to Side	22.5°

COOLING SYSTEM

Coolant Capacity of Jacket (Engine only) - liter (U.S.gal)	83	(21.9)
Coolant Capacity of Air cooler (Engine only) - liter (U.S.gal)	17	(4.5)
Maximum External Friction Head at Engine Outlet - kgf/cm ² (psi)	(For Jacket and Air Cooler)	
	0.35	(5.0)
Maximum Static Head of Coolant above Crankshaft Center - m(ft)	10	(32.8)
Standard Thermostat (modulating)Range of Jacket - °C(°F)	71 ~ 85	(160 ~ 185)
Standard Thermostat (modulating)Range of Air Cooler - °C(°F)	35 ~ 50	(95 ~ 122)
Maximum Coolant Temperature at Engine Outlet of Jacket - °C(°F)	98	(208)
Minimum Coolant Expansion Space - % of System Capacity	(For Jacket and Air Cooler)	
	10	(0.4)
Maximum Coolant Temperature at Intercooler Inlet, PTAW type - °C(°F)	45	(113)
Maximum Air Restriction on Discharge Side of Radiator and Fan - mm H ₂ O(in.H ₂ O)	10	(0.4)

Certified for US EPA-Tier 2 / Constant Speed

Standard Model [1000kWe/60Hz]

mitsubishi

S12H-Y2PTAW-1

SPECIFICATION SHEET

DIESEL ENGINES

FUEL SYSTEM

Fuel Injector	_____	Mitsubishi Electrical controlled Unit injector × 12
Maximum Suction Head of Feed Pump - mm Hg (in. Hg)	_____	75 (3.0)
Maximum Static Head of Return Pipe - mm Hg (in.Hg)	_____	220 (8.7)

STARTING SYSTEM

Battery Charging Alternator - V- Ah	_____	24-30
Starting Motor Capacity - V - kW	_____	24-7.5 × 2
Maximum Allowable Resistance of Cranking Circuit - m	_____	1.5
Recommended Minimum Battery Capacity		
At 5°C (41°F) and above - Ah	_____	300
Below 5°C (41°F) through - 5°C (23°F)	_____	600

The specifications are subject to change without notice.

APPLICATION : GENERATOR

Pub. No. T13-0633-E

Certified for US EPA-Tier 2 / Constant Speed

Standard Model [1000kWe/60Hz]

S12H-Y2PTAW-1

SPECIFICATION SHEET

MITSUBISHI

DIESEL ENGINES

ENGINE RATING

All data represent net performance with standard accessories such as air cleaner, inlet /exhaust manifolds, fuel oil system, L.O. pump, etc. under the condition of 100kPa(29.6inHg) barometric pressure, 77°F(25°C) ambient temperature and 30% relative humidity.

ITEM	UNIT	STAND-BY POWER	PRIME POWER		
		60Hz	60Hz		
Engine Speed	rpm	1800	1800		
No. of Cylinders		12			
Bore	mm (in.)	150 (5.91)			
Stroke	mm (in.)	175 (6.89)			
Displacement	liter (in. ³)	37.11 (2265)			
Brake Horse power without Fan	HP (kW)	1528 (1140)	1389 (1036)		
Brake Mean Effective Pressure without Fan	kgf/cm ² (psi)	20.9 (297)	19.0 (270)		
Mean Piston Speed	m/s (ft/min)	10.5 (2067)	10.5 (2067)		
Maximum Regenerative Power Absorption Capacity without Fan	HP (kW)	145 (108)	145 (108)		
Intake Air flow	m ³ /min (CFM)	102 (3602)	93 (3284)		
Exhaust Gas Flow	m ³ /min (CFM)	270 (9534)	247 (8722)		
Coolant Flow	liter/min (U.S. GPM)	1450 (383)	1450 (383)		
Coolant Flow to Intercooler (PTAW only)	liter/min (U.S. GPM)	500 (132)	500 (132)		
Cooling Air Flow (Std. Fan)	m ³ /min (CFM)	-	-		
Allowable Fan Loss Horse Power	HP (kW)	54 (40)	54 (40)		
Radiated Heat to Ambient	kcal/hr (BTU/min)	76835 (5082)	70236 (4645)		
Heat Rejection to Coolant	kcal/hr (BTU/min)	358563 (23715)	327770 (21678)		
Heat Rejection to Air Cooler (PTAW Version)	kcal/hr (BTU/min)	281728 (18633)	257534 (17033)		
Heat Rejection to Exhaust	kcal/hr (BTU/min)	863831 (57133)	794890 (52573)		
Noise Level (1 m height & distance) (excludes, Intake,Exhaust & Fan)	dB(A)	113	111		

The specifications are subject to change without notice.

APPLICATION : GENERATOR

Pub. No. T13-0633-E